

BEST AVAILABLE COPY

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-4. (canceled)

5. (currently amended)

An apparatus for providing support between a first structure and a second structure, comprising:

a first section having a first group of at least one magnetic frame member, the first section being coupled to the first structure; and

a second section having a second group of at least one magnetic frame member, the second section being coupled to the second structure,

wherein the first and second sections present magnetic force therebetween,

wherein the second group of at least one magnetic frame member is provided within the first group of at least one magnetic frame member,

wherein the first group of at least one magnetic frame member has a first direction of magnetic poles, the second group of at least one magnetic frame member has a second direction of magnetic poles, and the first direction is opposite to the second direction,

wherein the first section includes a first number of at least one magnetic frame member, the second section includes a second number of at least one magnetic frame member, and a difference between the first number and the second number is no more than 1, and

The apparatus of claim 4,

wherein the first number is more than 1, the second number is more than 1, a first pitch of the magnetic frame members included in the first group is smaller than a second pitch of the magnetic frame members included in the second group.

6. (original) The apparatus of claim 5, wherein a ratio of the second pitch to the first pitch is more than 1 and less than 1.5.

7. (canceled)

8. (currently amended) An apparatus for providing support between a first structure and a second structure, comprising:

a first section having a first group of at least one magnetic frame member, the first section being coupled to the first structure; and

a second section having a second group of at least one magnetic frame member, the second section being coupled to the second structure,

wherein the first and second sections present magnetic force therebetween,

wherein the second group of at least one magnetic frame member is provided within the first group of at least one magnetic frame member,

wherein the first group of at least one magnetic frame member has a first direction of magnetic poles, the second group of at least one magnetic frame member has a second direction of magnetic poles, and the first direction is opposite to the second direction,

wherein the first section has a third group of at least one magnetic core, and

The apparatus of claim 7,

wherein the third group of at least one magnetic core is provided within the second group of at least one magnetic frame member.

9. (original) The apparatus of claim 8, wherein the third group of at least one magnetic core has a third direction of magnetic poles, and the third direction is the same as the first direction.

10. (original) The apparatus of claim 9, wherein the first section includes a third number of at least one magnetic core, and the third number is the same as the first number.

11. (original) The apparatus of claim 10, wherein the third number is more than 1, a third pitch of the magnetic frame members included in the third group is smaller than a second pitch of the magnetic frame members included in the second group.

12. (original) The apparatus of claim 11, wherein a ratio of the second pitch to the third pitch is more than 1 and less than 1.5.

13. (original) The apparatus of claim 12, wherein the first, second and third numbers are 4, 3 and 4, respectively.

14-17. (canceled)

18. (currently amended) A method of providing support between a first structure and a second structure, comprising:

coupling a first section to the first structure, the first section having a first group of at least one magnetic frame member; and

coupling a second section to the second structure, the second section having a second group of at least one magnetic frame member,

wherein the first and second sections present magnetic force therebetween,

wherein the second group of at least one magnetic frame member is provided within the first group of at least one magnetic frame member,

wherein the first group of at least one magnetic frame member has a first direction of magnetic poles, the second group of at least one magnetic frame member has a second direction of magnetic poles, and the first direction is opposite to the second direction,

wherein the first section includes a first number of at least one magnetic frame member, the second section includes a second number of at least one magnetic frame member, and a difference between the first number and the second number is no more than 1, and

The method of claim 17,

wherein the first number is more than 1, the second number is more than 1, a first pitch of the magnetic frame members included in the first group is smaller than a second pitch of the magnetic frame members included in the second group.

19. (original) The method of claim 18, wherein a ratio of the second pitch to the first pitch is more than 1 and less than 1.5.

20. (canceled)

21. (currently amended) A method of providing support between a first structure and a second structure, comprising:

coupling a first section to the first structure, the first section having a first group of at least one magnetic frame member; and

coupling a second section to the second structure, the second section having a second group of at least one magnetic frame member,

wherein the first and second sections present magnetic force therebetween,

wherein the second group of at least one magnetic frame member is provided within the first group of at least one magnetic frame member.

wherein the first group of at least one magnetic frame member has a first direction of magnetic poles, the second group of at least one magnetic frame member has a second direction of magnetic poles, and the first direction is opposite to the second direction.

wherein the first section has a third group of at least one magnetic core, and

~~The method of claim 20,~~

wherein the third group of at least one magnetic core is provided within the second group of at least one magnetic frame member.

22. (original) The method of claim 21, wherein the third group of at least one magnetic core has a third direction of magnetic poles, and the third direction is the same as the first direction.

23. (original) The method of claim 22, wherein the first section includes a third number of at least one magnetic core, and the third number is the same as the first number.

24. (original) The method of claim 23, wherein the third number is more than 1, a third pitch of the magnetic frame members included in the third group is smaller than a second pitch of the magnetic frame members included in the second group.

25. (original) The method of claim 24, wherein a ratio of the second pitch to the third pitch is more than 1 and less than 1.5.

26. (original) The method of claim 25, wherein the first, second and third numbers are 4, 3 and 4, respectively.

27. (currently amended) A method for making an object using a lithography process, wherein the lithography process utilizes [[the]] a method [[of claim 14]] of providing support between a first structure and a second structure, the method including

coupling a first section to the first structure, the first section having a first group of at least one magnetic frame member, and

coupling a second section to the second structure, the second section having a second group of at least one magnetic frame member,

wherein the first and second sections present magnetic force therebetween.

28. (currently amended) A method for patterning a wafer using a lithography process, wherein the lithography process utilizes [[the]] a method [[of claim 14]] of providing support between a first structure and a second structure, the method including

coupling a first section to the first structure, the first section having a first group of at least one magnetic frame member; and

coupling a second section to the second structure, the second section having a second group of at least one magnetic frame member; wherein

the first and second sections present magnetic force therebetween.

29-31. (canceled)

32. (new) An apparatus that supports a first structure relative to a second structure, comprising:

a first member that includes a first magnetic member having a magnetic pole; and

a second member that includes a cylindrical shell having a magnetic member;

wherein the direction of the magnetic pole of the first magnetic member is substantially parallel to a support direction of the first structure,

wherein a cross section of the first member cut by a plane perpendicular to the support direction has a circular outer periphery,

wherein the cylindrical shell surrounds at least an outer surface of a part of the first member,

wherein the first section and the second section present magnetic force therebetween, and

wherein one of the first section and the second section is connected to the first structure, and the other of the first section and the second section is connected to the second structure.

33. (new) The apparatus of claim 32, wherein a shape of the first member is column.

34. (new) The apparatus of claim 32, wherein the cylindrical shell includes a second magnetic member that has a magnetic pole.

35. (new) The apparatus of claim 33, wherein the direction of the magnetic pole of the second magnetic member is substantially parallel to a support direction of the first structure.

36. (new) The apparatus of claim 32, further comprising:

a third section that includes a second cylindrical shell having a magnetic member,

wherein the second cylindrical shell surrounds at least an outer surface of a part of the second member,

wherein the third section being coupled to the one of the first and second structures to which the first member is connected, and

wherein the second section and the third section present magnetic force therebetween.

37. (new) A method of providing support between a first structure and a second structure, comprising:

connecting a first member to the first structure; and

connecting a second member to the second structure,

wherein the first member includes a first magnetic member that has a magnetic pole,

wherein the direction of the magnetic pole of the first magnetic member is substantially parallel to a support direction of the first structure,

wherein a cross section of the first member cut by a plane perpendicular to the support direction has a circular outer periphery,

wherein the second member includes a cylindrical shell that has a magnetic member,

wherein the cylindrical shell surrounds at least an outer surface of a part of the first member, and

wherein the first section and the second section present magnetic force therebetween.

38. (new) The method of claim 37, wherein a shape of the first member is column.

39. (new) The method of claim 37, wherein the cylindrical shell comprises a second magnetic member that has a magnetic pole.

40. (new) The method of claim 37, wherein the direction of the magnetic pole of the second magnetic member is substantially parallel to a support direction of the first structure.

41. (new) The method of claim 37, further comprising:

connecting a third section to the one of the first and second structures to which the first member is connected,

wherein the third section includes a second cylindrical shell that has a magnetic member,

wherein the second cylindrical shell surrounds at least an outer surface of a part of the second member; and

wherein the second section and the third section present magnetic force therebetween.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.